

Configuration summary

Mat. no.	Description Order code	Quantity	Unit
71262968	Promag P 300, 5P3B50, DN50 2" 5P3B50-AAIBAAAFADDEA1K0AA2	1	PC

Details

Curr. output 1	Volume flow	
Current span	4...20 mA NAMUR	
4 mA value		0 dm3/min
20 mA value		300 dm3/min
Failsafe mode current output	Max.	
Damping output 1		1 s
Format display	1 value, max. size	
Value 1 display	Volume flow	
Value 2 display	None	
Value 3 display	None	
Value 4 display	None	
Display damping		0 s
Totalizer 1		
Unit	dm3	
Operating mode totalizer	Net flow total	
Failure mode	Stop	
Totalizer 2		
Unit	dm3	
Operating mode totalizer	Net flow total	
Failure mode	Stop	
Totalizer 3		
Unit	dm3	
Operating mode totalizer	Net flow total	
Failure mode	Stop	

010	Approval; Transmitter + Sensor:	AA	Non-hazardous area
015	Power Supply:	I	AC 100...240V/DC 24V
020	Output; Input 1:	BA	4-20mA HART
021	Output; Input 2:	A	W/o;
022	Output; Input 3:	A	W/o;
030	Display; Operation:	F	4-line illum.; touch control
040	Housing:	A	Alu, coated

050	Electrical Connection:	D	Thread NPT1/2
060	Liner:	E	PTFE
070	Process Connection:	A1K	Cl.150, carbon steel, flange ASME B16.5
075	Electrodes:	0	1.4435/316L
080	Flow Calibration:	A	0.5%
480	Device Model:	A2	2