

Siemens
EcoTech



SIMATIC ET 200SP HA, analog HART input module, AI 16xI 2-wire HART HA, suitable for terminal block H1, M1, color code CC01, channel diagnostics, 16-bit, +/-0.1%,

General information	
Product type designation	AI 16 x I 2-wire mA HART
Firmware version	V1.1
• FW update possible	Yes; The firmware update can take more than 5 minutes.
Usable terminal block	type H1, M1, N0, H0, M0 (for details see the system manual)
Color code for module-specific color-coded label	CC01
Product function	
• I&M data	Yes; I&M0 to I&M3
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V16
• STEP 7 configurable/integrated from version	V5.6
• PCS 7 configurable/integrated from version	V9.0
• PCS neo can be configured/integrated from version	V3.0
• PROFINET from GSD version/GSD revision	GSDML V2.3
Redundancy	
• Redundancy capability	Yes; With TB type M1
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	80 mA; without sensor supply
Current consumption, max.	90 mA; without sensor supply
Encoder supply	
24 V encoder supply	
• 24 V	Yes
• Short-circuit protection	Yes; Electronic (response threshold 0.7 A to 1.5 A)
• Output current per channel, max.	0.5 A
• Output current per module, max.	2 A
Power loss	
Power loss, typ.	4.5 W; without sensor supply
Address area	
Address space per module	

- Address space per module, max.
- Address space per module with HART, max.
- Address space per module with MultiHART, max.

34 byte; 32-byte inputs and 2 bytes for QI information
 74 byte; 32-byte inputs and 2 bytes for QI information, 40-byte inputs for HART
 41 byte; 32-byte inputs for HART and 2 bytes for QI information, 6-byte inputs for HART, and 1-byte output for MultiHART command

Analog inputs

Number of analog inputs	16
permissible input current for current input (destruction limit), max.	30 mA
Input ranges (rated values), currents	
• 0 to 20 mA — Input resistance (0 to 20 mA) • 4 mA to 20 mA — Input resistance (4 mA to 20 mA)	Yes; 16 bit incl. sign 250 Ω Yes; 16 bit incl. sign 250 Ω
Cable length	
• shielded, max.	800 m; with unshielded cables up to 800 m, remember that (external) EMC loads can cause incorrect measured values

Analog value generation for the inputs

Measurement principle	integrating (Sigma-Delta)
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max. • Integration time, parameterizable	16 bit; 15 bit at 0 ... 10 mA and 60 Hz interference suppression Yes; channel by channel
Smoothing of measured values	
• parameterizable	Yes; none, weak, medium, strong, channel-by-channel

Encoder

Connection of signal encoders	
• for current measurement as 2-wire transducer	Yes

Errors/accuracies

Linearity error (relative to input range), (+/-)	0.01 %
Temperature error (relative to input range), (+/-)	0.005 %/K
Crosstalk between the inputs, min.	60 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
Operational error limit in overall temperature range	
• Current, relative to input range, (+/-)	0.5 %
Basic error limit (operational limit at 25 °C)	
• Current, relative to input range, (+/-)	0.1 %

Interrupts/diagnostics/status information

Diagnostics function	Yes
Alarms	
• Diagnostic alarm • Limit value alarm	Yes Yes; two upper and two lower limit values in each case
Diagnoses	
• Monitoring the supply voltage • Wire break • Short-circuit • Overflow/Underflow	Yes Yes; channel by channel Yes; Channel-by-channel, short-circuit of the encoder supply to ground or of an input to the encoder supply Yes; channel by channel
Diagnostics indication LED	
• MAINT LED • Monitoring of the supply voltage (PWR-LED) • Channel status display • for channel diagnostics • for module diagnostics	Yes; Yellow LED Yes; green PWR LED Yes; green LED Yes; red LED Yes; green/red DIAG LED

Potential separation

Potential separation channels	
• between the channels • between the channels and backplane bus • Between the channels and load voltage L+	No Yes No

Isolation

Isolation tested with	1 500 V DC/1 min, type test
-----------------------	-----------------------------

Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-40 °C
• horizontal installation, max.	70 °C; Observe derating
• vertical installation, min.	-40 °C
• vertical installation, max.	60 °C; Observe derating
Dimensions	
Width	22.5 mm
Height	115 mm
Depth	138 mm
Weights	
Weight, approx.	148 g
Classifications	

	Version	Classification
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596

Approvals / Certificates
General Product Approval



[Miscellaneous](#)



[Declaration of Conformity](#)



General Product Approval



[China RoHS](#)

[Miscellaneous](#)



[Manufacturer Declaration](#)

For use in hazardous locations



[Declaration of Conformity](#)



For use in hazardous locations	Maritime application
--------------------------------	----------------------

[Miscellaneous](#)



[NK / Nippon Kaiji Kyokai](#)

Maritime application	Environment
----------------------	-------------



[CCS \(China Classification Society\)](#)



last modified:

11/24/2025